



**RLM RT14 GNLX** H: 13.50 W: 14 E: 22.50 MC: 2.75

**Description**

14" Tapered, 14" L-arm

**Specifications**

- Housing** Spun aluminum shade with extruded arm and cast canopy\*
- Diffuser/Optics**
  - FR - Frosted Glass
  - Lensed LED (no diffuser) for Dry locations only
- Light Source** LED
- Max Watts** 9.62
- Electrical** TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)

**Ordering Guide:** Choose from each category, using designated code to specify.

RT14 GNLX					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

- FR - Frosted glass
- LOZ - Lensed LED (no diffuser)

**Light Source**

- TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
- TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
- TL8 - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
- TL10 - 9.62W/30K 1790 Lm, 120V dimmable

**Finish**

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded\***
- RAL - [Specify Color #](#)
- UPG - [Select Color from Luraline Palette](#)
- Premium\***
- CCM - Custom Color
- CIC - [Inner Color](#)
- CTC - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)

NOTES:  
\*Driver is housed in extended aluminum canopy (not shown)