



RLM RT14X P2 H: 19 W: 14 E: 41

Description

14" Tapered, Double U-arm postlight (slips 3")

Specifications

- Housing** Spun aluminum shade with extruded arm and cast fitter
- Diffuser/Optics**
 - Bare lamp (no diffuser) for Dry locations only
 - Clear glass
 - Frosted Glass cylinder
- Light Source** LED
- Max Watts** 9.62 X 2
- Electrical** TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
- Mounting** Slips 3" OD (PX Series) poles - order separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)

Ordering Guide: Choose from each category, using designated code to specify.

RT14X P2				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare-lamp (no diffuser)
- CL** - Clear glass
- FR** - Frosted glass

Light Source

- 2TL3 HO** - 6.08W/40K 1964 Lm, 0-10V dimmable
- 2TL3** - 3.11W/30K 603 Lm, 0-10V dimmable
- 2TL5 HO** - 9.2W/40K 2408 Lm, 120V dimmable
- 2TL5** - 9.4W/30K 1708 Lm, 120V dimmable
- 2TL6 HO** - 12.32W/40K 3176 Lm, 120V dimmable
- 2TL6/P** - 12.64W/30K 2416 Lm, 120V dimmable
- 2TL6** - 12.64W/30K 2416 Lm, 120V dimmable
- 2TL8 HO** - 15.5W/40K 3772 Lm, 120V dimmable
- 2TL9 HO** - 18.72W/40K 4358 Lm, 120V dimmable
- 2TL10** - 19.24W/30K 3580 Lm, 120V dimmable

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 2DIM010** LED 4-wire 0-10V Dimming - 120-277V
- 35K** Neutral White
- CG3** Cast aluminum guard (requires diffuser)
- SSP** 10KV 120-277V Supplemental Surge Protection