



Legacy Product SH16 CM H: 10.50 W: 16

Description

MOQ of 24 pcs. required

Specifications

Housing	Stamped steel fitter and canopy		
Diffuser/Optics	Opal Glass		
Light Source	GUL	MBL	Medium Base
Max Watts	15	18	100
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only		

Ordering Guide: Choose from each category, using designated code to specify.

SH16 CM

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser/Optics

OP - Opal Glass

Light Source

- MB25 A - 25W MAX. MED base (A19 lamp by others)
- MBL9.8A - 9.8W/30K 800 Lm OmniLED
- MBL10A JA8 - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL11A - 11W/30K 1100 Lm OmniLED
- GUL11A - 11W/27K 1100 Lm GU24 OmniLED
- MBL13A JA8 - 13W/30K 1100 Lm 90+ CRI OmniLED
- GUL15A - 15W/27K 1600 Lm GU24 OmniLED
- MBL18A JA8 - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB - 100W Max Incand A (by others)

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)