



**Decorative SP12** H: 12 W: 12

**Description**

**Specifications**

<b>Housing</b>	Injection-molded polycarbonate	
<b>Diffuser/Optics</b>	White acrylic	
<b>Light Source</b>	MBL	Medium Base
<b>Max Watts</b>	10	100
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.	
<b>Mounting</b>	Slips 3" OD (P Series) poles - order separately	
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	

**Ordering Guide:** Choose from each category, using designated code to specify.

SP12					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**  
**WAC** - White Acrylic

**Light Source**  
**MB25 A** - 25W MAX. MED base (A19 lamp by others)  
**MBL9.8A** - 9.8W/30K 800 Lm OmniLED  
**MBL10A JAB** - 10W/30K 800 Lm 90+ CRI OmniLED  
**MB** - 100W Max Incand A (by others)

**Finish**  
**Standard**  
**BL** - Black  
**WH** - White

**Extras (Order Separately)**